



CE

Customer

Demo Unit RREV
1133 Rankin Street
St Paul MN 55116
Bob Haselman
651-690-1867

DEALER

Road Rescue Emergency Vehicles
1133 Rankin Street Suite D-1
St Paul MN 55116
Bob Haselman
651-690-1867

Chassis: 2009 CHEV G4500 100"C/A, 159"W/B (Cutaway), 14,200 GVWR
Module: Ultramedic III - 170"L x 96"W, Chevy CG3300, Walk-Through

Cat. Sec. Opt. Description

INFORMATION

. 1 . 200 2009 Option Package w/ Pan Formed Doors and Extruded Jambs. Includes the following:

- 1.21.35 - Thinsulate in Cab Ceiling
- 3.3.14 - Structural Roof Radius Extrusion.
- 3.3.15 - 3M Extreme Bonding Tape
- 3.3.16 - Sub-Floor Gusset Supports
- 3.6.40 - 2009 Box Pan Formed, Hidden Hinge Entrance Door
- 3.6.41 - Stainless Steel Kick Panels, Entrance Doors
- 3.6.22 - Coil Cord Door to Door Jamb
- 3.8.5 - Whelen Mini LED Step Well Light
- 3.15.20 - Extruded Crash Rail End Caps
- 3.19.20 - Reduced Walkthrough Door for Fluid Dam
- 3.19.21 - Cab to Module Fluid Dam
- 3.20.5 - Whelen Mini LED License Plate Light
- 4.2.20 - 2009 Box Pan Formed, Hidden Hinge Compartment Doors
- 4.2.22 - Polished Chrome Door Handles w/ Floating Cam
- 4.6.11 - #1 Compartment Storage Panel Latches
- 5.1.19 - Restocking Felt Track and Slam Latches
- 5.1.20 - Stainless Steel Interior Pull Ring Latches
- 5.1.21 - Interior Cushion Fastening
- 5.6.11 - Ceiling Medical Devise Rail
- 5.6.12 - Seamless Headliner
- 5.10.5 - Anti-Microbial Grab Bars, 'L' Bars
- 5.13.7 - Action Wall Medical Devise Rail
- 5.16.45 - Squad Bench Medical Devise Rail
- 5.17.2 - Anti-Microbial 'A' Bar
- 5.18.8 - Right Stack Hidden Air Intake
- 5.19.15 - Wise Vacuum Formed Seat
- 8.4.37 - Improved Module Harness Routing
- 8.4.38 - PC Switch Panel Display and Hall Effect Sensor
- 9.70.25 - Chrome Trim Rings Emergency Lights
- 10.1.23 - Whelen Mini LED Marker Lights
- 10.2.19 - Chrome Trim Rings Scene Lights
- 11.1.9 - Ceiling Lighting Layout
- 11.1.10 - Restocking Timer

Print Date: 6/23/2009

1

Unit No. 0

Database Da 6/12/2009 10:20:42 .

Chassis: 2009 CHEV G4500 100"C/A, 159"W/B (Cutaway), 14,200 GVWR

Module: Ultramedic III - 170"L x 96"W, Chevy CG3300, Walk-Through

Cat. Sec. Opt. Description

- . 1 . 500 SPECIAL - WEMSA member discount. Discount paid directly by WEMSA.

CHASSIS

1. 1 . 4003 SPECIAL - 2009 CHEVROLET G4500 Cutaway 4X2. 100" C/A, 159" WB. 14,200 GVWR, Duramax 6.6L diesel engine rated at 330 HP, 4 Speed electronically controlled automatic transmission with overdrive and tow/haul mode, Heavy duty locking rear differential, 3.73:1 ratio, External engine oil and transmission oil coolers. Engine block heater, dual (2) 145A alternators, Auxiliary heat/AC provisions. High back adjustable bucket seats, Cloth and vinyl color keyed, Cruise control, Adjustable/ tilt steering wheel, Power windows and door locks, Daytime running lights, OEM manual Hi Idle switch on steering wheel. AM/FM stereo radio w/digital clock, OEM rubber floor, Spare tire
NOTE: Includes Velvac 2020XG Deluxe Black Mirrors, Heated, Remote, Lighted Turn Signals.
ULTRAMEDIC ONLY

SAFETY OPTIONS

1. 22 . 64 Anti-theft Device w/Engine Kill
- Removable Key w/Engine Running, Includes Enable Switch.
2008-up Chevy CG3300 Only

MODULE TYPE

2. 1 . 450 SPECIAL - Ultramedic III - 170"L x 96"W Type III Walk-Through Module
Includes 10" Cab Recess.
Chevy CG3300 - 158"WB

EXTERIOR MODULE CONSTRUCTION

3. 3 . 83 Fuel Fill Splash Protection Plate
Diamond plate fuel fill splash protection plate installed below Cast Products fuel fill bezel. Sikaflex adhesive/sealant shall be used to mount the plate and to seal plate edges.

MODULE ENTRANCE DOORS

3. 6 . 65 Non-Remote Power Door Locks for Entrance Doors
- Install power door locks in side and rear entrance doors. Includes (2) lock/unlock switches, one at side door and one at rear door. Also includes (1) hidden switch in rear license frame for unlock function only. System will be tied to OEM chassis power locks so that both systems operate as one. Available with all models.
NOTE: Choose Separate Option for Power Door Locks on exterior compartments.

WINDOWS

3. 9 . 20 "Dry Erase" (2) Piece Sliding Window Covers
- Over curbside squad bench window in sliding glass track. Each side recessed behind the corresponding side's backrest cushion when in the open position. Writing board to be polished white laminate on .125" aluminum.
3. 9 . 31 Fixed Privacy Tint Window, Over the Squad Bench
- Fixed Privacy tint window that is approximately 14"H x 33.5"L installed in the curbside wall over the squad bench
NOTE: This is an applied film. The privacy tint is laminated on the glass surface.
3. 9 . 74 Limo Privacy Tint Side and Rear Doors.
- Sliding side door window and sliding rear door windows to have Limo Privacy Tint installed. NOTE: Side door sliding, Rear door sliding.

Chassis: 2009 CHEV G4500 100"C/A, 159"W/B (Cutaway), 14,200 GVWR

Module: Ultramedic III - 170"L x 96"W, Chevy CG3300, Walk-Through

Cat. Sec. Opt. Description

BUMPER AND REAR STEP CONSTRUCTION

3. 12. 18 Recessed 9" Flip-up Rear Bumper Pocket.
- The 9" grip strut center section of the bumper shall flip up into a recessed pocket in the lower diamond plate wrapper. The recess shall be finished in polished diamond plate to match the wrapper and shall be deep enough to make the flipped up bumper flush with the outside of the vehicle.

INSULATION

3. 13. 23 Thinsulate Acoustical Wall Insulation Package - Add layer of Thinsulate material over standard wall insulation to improve sound deadening. Thinsulate layer shall be installed over wall tubes in a continuous sheet . Includes changing wall panels to .125" aluminum.

COMBINATION RUB RAIL AND FENDER RING

3. 15. 51 Crash Rail and Fender Ring Scotchlite Color:

White Scotchlite - (STANDARD)

SPLASH GUARDS AND RUNNING BOARDS

3. 16. 29 Grip Strut Running Board
- Add 5" grip strut inserts to the Standard NFPA diamond plate running boards. The inserts are to be welded on the bottom side of the diamond plate horizontal surface so that the welds are not visible. Includes OEM style mudflaps modified and installed on the front end of the running board to protect grip strut insert from wheel splash.
Chevy CG3300

#4 COMPARTMENT

4. 9. 1 Full Height #4 Compartment with Interior Upper left #4 Cabinet (Standard)
- #4 Compartment to be full height to bottom of upper left #4 cabinet. Compartment includes (1) adjustable shelf. (STANDARD)

#8 COMPARTMENT

4. 14. 14 'A' Style Full Height #8 Compartment.
- #8 Compartment to be full height to bottom of locking drug cabinet. Compartment door allows access to the interior ALS cabinet. The interior ALS cabinet to include (2) adjustable shelves. (STANDARD Ultramedic, Promedic)

HEADLINER

5. 6. 11 Ceiling Medical Devise Rail
- Install a near flush mount Medical Devise rail Medical Devise Rail system over the primary cot. Each side of the track will have an accent stripe. The track system to be recessed and run the entire length of the module with the sole intent of providing easy access to allow the medical personnel to quickly access equipment for administering aid to the patient.
Installed as standard will be (1) IV Hanger, (3) Patient Lights focused at head, torso and legs, and (2) antenna access plates.
See separate options for additional IV hangers, oxygen outlet and AM/FM speakers.
(2009 STANDARD)

FLOORING

5. 7. 51 Loncoin II Flecks UV Flooring Choice
Loncoin floors are commercial grade anti-skid materials.

Loncoin II Flecks UV Sapphire. 152UV

Chassis: 2009 CHEV G4500 100"C/A, 159"W/B (Cutaway), 14,200 GVWR

Module: Ultramedic III - 170"L x 96"W, Chevy CG3300, Walk-Through

Cat. Sec. Opt. Description

LEFT STACK AREA #1

- 5. 12. 3 Left Stack to include (1) adjustable shelf in upper section. Both sections shall have double solid aluminum, Formica covered doors with a locking lever latch on the upper doors and a non-locking lever latch on the lower doors.
(STANDARD Ultramedic)

SQUAD BENCH AREA

- 5. 16. 82 Overhead Squad Bench Cabinet for 72" Headroom - Non KKK compliant. Approximately 12"D x 12"H x length of squad bench. Cabinet mounted at ceiling level over the squad bench. Distance between top of squad bench cushion to bottom of cabinet cushion to be minimum of 39".
NOTE: Includes restocking feature.

BIOHAZARD

- 5. 17. 210 Glove Butler, (3) Over Curbside Entry
- (3) Glove Butler II glove boxes installed above the side module entrance door with drop down door and (2) 2" Round non-locking Stainless Steel pull ring slam latches. Door to be bottom hinged to tip out for restocking. Access holes to be cut in door for glove removal.

CURBSIDE RIGHT STACK STORAGE #8

- 5. 18. 24 Delete Lower ALS Doors
- Delete the standard hinged doors in the lower ALS.
- 5. 18. 500 SPECIAL (3) Seat Belt restraints over each opening of the lower ALS cabinet.

ATTENDANT SEAT

- 5. 19. 16 Wise vacuum formed Attendant/Child seat #WM1791 with 6 degree back and 2 point seat belt mounted on a #WM1612 frame style swivel base.
- 5. 19. 16 Wise seat to be Ash Gray

INTERIOR COLORS

- 5. 20. 51 Laminate color choices.
 - . . Wilsonart Dove Gray, Matte Finish #D92-60
(STANDARD)
NOTE: Replaces Matte Fog 961-58
- 5. 20. 53 Upper Band Vinyl Color Choice for cabinets and stitched cushions.
 - . . Cobalt Blue
- 5. 20. 55 Vacuum Formed Lower Band Vinyl Color Choice
All lower band seat cushions and back rests to be vacuum formed and secured with Velcro.
Includes Squad bench seats, squad bench back rest, CPR seat, CPR backrest and hip cushions.
 - . . Ash Gray

MISC. INTERIOR OPTIONS

- 5. 21. 500 SPECIAL - Dealer Installed Option, Restock security loops on all interior cabinets.
RREV

Chassis: 2009 CHEV G4500 100"C/A, 159"W/B (Cutaway), 14,200 GVWR

Module: Ultramedic III - 170"L x 96"W, Chevy CG3300, Walk-Through

Cat. Sec. Opt. Description
COMMUNICATION

6. 6 . 100 Audiovox, ASA Voyager VCCS-130 Color back-up Camera.
- Camera mounted exterior over the rear entry doors and connected to SD II display in cab console.
Video display wired to turn camera on when vehicle is placed in reverse.
Note: This option requires Option 8.4.42 (Smart Display II with video inputs)
6. 6 . 500 SPECIAL - DEALER OPTION: Install customer supplied two-way radio and cell phone equipment. Includes final connections and soldering antenna bases. Radio/cell phone programming is not included.

RADIO AND CLOCKS

6. 7 . 54 Trintec 12/24 Hour Clock, Battery Powered, Over Rear Doors
- Trintec 6" inch, dry cell battery operated electric 12/24 hour analog clock with sweep second hand, recessed in cushion over rear doors.

FRONT CONSOLE

8. 1 . 52 SPECIAL - Custom Floor Console, to Accommodate Switch Panel ,Siren and Custom Layout
- Formed and Welded Aluminum Driver's Console ILOS. Console to Accommodate Switch Panel ,Siren, computer mount and Custom Layout.

PROVIDE LAYOUT AND DIMENSIONS.

DRIVER'S CONTROL PANEL

8. 2 . 91 Gooseneck Light, 12" Little Lite
- 12 inch Federal Signal LittleLite # LF12TRB. High intensity gooseneck light with removable red filter. Lamp base includes Hi-Lo dimmer. Cab switch console.

ATTENDANT CONTROL PANEL

8. 3 . 22 SPECIAL - Smart System II, (1) Additional Rear Control Panel
- (1) Additional Class I , Smart System II Rear Control Panel, located just below the over squad bench cabinet at the head end. Includes custom cabinet angled towards rear.
Mount standard panel on swivel at action counter.

POWER DISTRIBUTION

8. 4 . 42 Smart Display II, w/LCD VGA Screen on front switch panel
- Road Rescue Smart Display II Multiplex electrical system.
Includes Micro-Touch Membrane Switches in Front and Rear Switch Panels
Digital Clock in Rear Panel, Remote Diagnostic Modem Installed
O2 Regulator/Transducer Mounted in #1 Compartment

INCLUDES VIDEO INPUTS FOR CAMERA OR GPS

NOTE: Program the battery shut-off circuit to remain on for 5 minutes after the ignition has been shut off. Shutting off the ignition will activate a timer that will leave the batteries on for five minutes so that the module dome lights can be left on for patient unloading/vehicle restocking.
(STANDARD ON SMART DISPLAY ONLY)

DRIVER'S COMPARTMENT STORAGE

8. 5 . 55 SPECIAL - Map Box Recessed into Top of Console.
A map box shall be recessed into the radio face plate in the front console. The box shall be approximately 12" x 6" in size, and approximately 8" deep. The interior of the box shall be painted white and shall include binning strips with (2) adjustable plexiglas dividers.

Chassis: 2009 CHEV G4500 100"C/A, 159"W/B (Cutaway), 14,200 GVWR

Module: Ultramedic III - 170"L x 96"W, Chevy CG3300, Walk-Through

Cat. Sec. Opt. Description

SIREN, SPEAKERS, AIR HORNS

9. 3 . 25 Siren, Whelen 295SLSA1, (STANDARD)
Whelen "Hands-Free" self diagnostic siren with NC microphone and 17 programmable Scan-Lock™ siren tones (STANDARD)

LIGHT BAR

9. 4 . 17 Front 90" Light Bar, Whelen 4500FL, Custom LED
- . . . SPECIAL - Front 90" Light Bar, Whelen 4500F, (9) Super LED
Includes (8) 700 LED Flashers Center Linear strobe powered from emitter
Lens colors: Red/Clear/Red/Red/Strobe/Red/Red/Clear/Red
NOTE: This option deletes the standard light bar.

FLASHERS - FRONT

9. 50 . 13 Add (2) Whelen 900 Super LED to module front. Upper outboard corners.
The light shall have internal flashers.
- . . . SPECIAL - Color: Red with Clear Lens

FLASHERS - DRIVER SIDE

9. 52 . 13 Driver side flashers - (2) Whelen 900 Super LED with internal flashers.
(1) in the upper forward and (1) in the upper rearward corners of the module.
- . . . SPECIAL - Color: Red with Clear Lens

FLASHERS - PASSENGER SIDE

9. 54 . 13 Passenger side flashers - (2) Whelen 900 Super LED with internal flashers.
(1) in the upper forward and (1) in the upper rearward corners of the module.
- . . . SPECIAL - Color: Red with Clear lens

FLASHERS - REAR

9. 56 . 13 Rear module flashers - (2) Whelen 900 Series Super LED with internal flashers.
Upper outboard corners.
- . . . SPECIAL - Color: Red with Clear Lens

REAR WINDOW FLASHERS

9. 58 . 13 Upper window flashers - (2) Whelen 900 Super LED warning lights with internal flashers to show though the upper portion of the rear door windows.
- . . . SPECIAL - Color: Red/White split wired to X pattern with each other.
Clear Lens
9. 58 . 33 Lower window flashers - (2) Whelen 900 Super LED warning lights with internal flashers to show though the lower portion of the rear door windows.
- . . . SPECIAL - Color: Red with Clear Lens

GRILLE LIGHTS

9. 60 . 13 Grille lights shall be Whelen 700 Super LED with Internal Flashers.
9. 60 . 13 Color: Red/ White Split. White to outside corners.

Chassis: 2009 CHEV G4500 100"C/A, 159"W/B (Cutaway), 14,200 GVWR

Module: Ultramedic III - 170"L x 96"W, Chevy CG3300, Walk-Through

Cat. Sec. Opt. Description

INTERSECTION LIGHTS - CAB

- 9. 62 . 13 Color: Red/ White Split. White to face forward.
- 9. 62 . 13 Cab Intersection Lights - Whelen 700 Super LEDs with internal flashers.

INTERSECTION LIGHTS - MODULE

- 9. 64 . 13 Wheel Well Intersection Lights - (2) Whelen 700 Super LEDs with internal flashers. Mounted above the rear wheel wells.
- . . Color: Red/ White Split. White to outside corners.

MISC EMERGENCY LIGHTS

- 9. 70 . 43 SPECIAL - There shall be a Tomar emitter The emitter will be ON with the Master Emergency switch and will be disengaged when the unit is in "park" or "neutral". A separate cutout switch will be installed on the front switch panel.
- 9. 70 . 104 (1) Whelen Talon Red/Clear TLN2RC mounted on the OEM dash
- 9. 70 . 500 SPECIAL -All LED Lens clear. All LEDs set to triple flash. All split color flash back and forth.

POWER SUPPLIES - SEQUENCERS

- 9. 80 . 52 Whelen #SSFPOS 'Wigwag' headlight flasher with high beam and night cutout. Model #SSF-2150 has been discontinued by Whelen. NOTE: Requires disconnection of Daytime running lights on all Ford chassis.

EXTERIOR AUTOMOTIVE LIGHTING

- 10. 1 . 110 SPECIAL - There shall be (2) TIR3 LED lights mounted on the front of the OEM mirrors that will operate with emergency lights on a separate switch. There shall be (1) Red TIR3 mounted on the driver side mirror and (1) White TIR3 mounted on the passenger side mirror. Wire lights to separate switch on sequencer. RREV

MODULE INTERIOR LIGHTING

- 11. 1 . 54 Dome Lights, (3) Whelen #86 Hi/Off/Lo
- (3) Additional Whelen #86 series high intensity patient checkout lights in ceiling of module over primary cot with separate 12V Hi/Off/Lo switch in rear switch panel. Wired 'On' with module.

HANDHELD SPOTLIGHT

- 11. 2 . 61 Streamlight SL-20X flashlight
- . . (2) Streamlight SL-20X flashlights #26010. Capable of 12VDC and 110VAC charging. Must choose option 11.2.91 or 11.2.92 for appropriate wiring. SPECIFY LOCATIONS Flashlights each come with (2) charging sleeves. Ship loose extra sleeves and cords.
- 11. 2 . 91 Flashlight Wiring
- . . SPECIAL - Wiring and install for (2) Flashlights. 12V Direct to Battery. Top of left stack.

110 VOLT OUTLETS

- 12. 2 . 1 Interior 110V-15A Receptacles.
(1) in the forward action wall and (1) at the top of lower Right Stack/ALS Cabinet on the plenum wall. (STANDARD).

Chassis: 2009 CHEV G4500 100"C/A, 159"W/B (Cutaway), 14,200 GVWR

Module: Ultramedic III - 170"L x 96"W, Chevy CG3300, Walk-Through

<u>Cat.</u>	<u>Sec.</u>	<u>Opt.</u>	<u>Description</u>
12.	2 .	51	SPECIAL - (1) additional illuminated interior 110VAC/15AMP duplex receptacle located on the plenum wall at the center shelf area of the lower right stack.

ONBOARD 110VAC POWER SUPPLY

12.	3 .	142	SPECIAL - Airpax Dimensions 'UL' listed 1200W inverter/Charger Model 12U12B3RT. Includes 55 Amp battery charger/conditioner, internal transfer relay, and remote status indicator panel. Add inverter switch to front switch panel in addition to the rear switch.
-----	-----	-----	--

COTS AND COT FASTENERS

14.	1 .	21	Cot Mount, Stryker #6370 Single Position ILOS Stryker #6370 single position cot fastener for a Stryker cot. Single Center position.
14.	1 .	80	SPECIAL - Stryker #6082MX PRO R3 Rugged Cot. IV Pole, PR, pocketed head end storage, head end O2 holder. Need to verify pricing.

DECALS

15.	3 .	500	Special - Average customer decal package cost. Add stone guard film to front of hood.
-----	-----	-----	--

MISCELLANEOUS

16.	3 .	51	Special - ITEM Flatbed freight from Marion, SC to St. Paul, MN
-----	-----	----	--

Call For Special Demo Pricing